

AUTO SHUT AIR SCREWDRIVER

TOKii®



- AUTO SHUT OFF
- TORQUE ADJUSTABLE
- WIDE RANGE OF TORQUE.
- SPECIAL CLUTCH INSTANT SHUTOFF
- LOW NOISE AND LESS AIR CONSUMPTION
- PB: PUSH TO START, L: LEVER START
- SOFT GRIP HELPS ALL DAY EASY WORKING FOR OPERATOR
- COLOR RINGS FOR IDENTIFICATION OF VARIOUS SET TORQUE TOOLS

Model No.	TOKii-T30PB	TOKii-T40PB	TOKii-T55PB	TOKii-T60PB	TOKii-T65PB	TOKii-T68PB
Torque Range (kgf-cm)	3-17	5-30	7-65	15-95	30-180	50-280
Free Speed (rpm)	1800	1000	1000	800	1400	1000
Accuracy (%)	±3	±3	±3	±3	±3	±3
Weight (g)	480	480	790	790	810	810
Length (mm)	180	180	215	215	215	215
Diameter (mm)	31	31	39	39	39	39
Air Hose Bore (Air Inlet 6 kg/cm ² (mm)	5	5	8	8	8	8
Air Consumption (m ³ /min)	0.28	0.28	0.55	0.55	0.55	0.55
Machine Screw Dia.	M2.2-M4.2	M2.8-M5.0	M2.9-M6.4	M4.1-M7.0	M5.0-M9.3	M6.0-M11.0
Tapping Screw Dia.	M1.7-M3.2	M2.2-M4.0	M2.6-M5.4	M3.1-M6.0	M4.0-M7.2	M4.9-M8.7