

Torque Tester **DI-4B-25**

Electric impact tool

Oil pulse tool

Air impact tool

Electric screwdriver



Manage the blow force and number that affect tightening

DI-4B-25 is a torque tester ideal for daily inspections of impact tool and electric driver.

Features

- Easy-to-see high brightness LED
- Simultaneously measure the blow force and blow number
- Come with the soft and hard joint
- Equipped with USB port

Ordering number

Model - Destination

Model	DI-4B-25
Measurement range	
Except impact tool	0.3~25.00 N·m
Impact tool	0.3~15.00 N·m (Note)
Accuracy	±0.5% (If 499 digit or less, ±3 digit.)
Power	Internal battery (Ni-MH)
Dimensions	150(W) × 220(D) × 74(H)
Accessories	Measurement joint HEX14-H250 Measurement joint HEX14-S250 Grease JT-GREASE Socket bit H17SCKTBIT-A20 HEX socket H17SOCKET-SQ9.5 AC adapter 6A-061WP12

(Note) When using an impact tool, please make sure that the tightening torque value of used tool does not exceed the measurement range of the tester.

Product specification detail

Destination

Code	Jx	Ox
Contents & measurement unit	(Used in Japan only) SI unit (N·m)	(Used in outside of Japan) SI unit (N·m) Weight unit (kgf·cm) Yard-pound unit (lbf·in)

* x specifies the AC adapter plug.

Code	1	2	3	4	5
Plug type	A type	A type (China)	C type	F type	G type

Accessories

HEX14 joint



[p.42]

Grease



[p.43]

Socket bit



[p.45]

HEX socket



[p.45]

AC adapter



[p.41]