

DISPENSER: TOKii-Y-801

Size: 195L x 216D x 60H
 Weight: 1.97kg
 Air input: 80-100Psi
 Dispense time: 0.01-31 seconds $\pm$ 0.1%
 Voltage: 110/220VAC
 Standard CE Approved

Features and Benefits

- * Dispenses all assembly fluids
- * Digital timer
- * Vacuum control for thin fluids
- * 1 Year function Warranty



DISPENSER: TOKii-820

Size: 215L x 225D x 90H
 Weight: 2.35kg
 Air input: 80-100Psi
 Dispense time: 0.001 - 99.99 seconds $\pm$ 0.1%
 Voltage: 110/220VAC
 Standard CE Approved

Features and Benefits

- * Microprocessor-based control
- * Time digital display from 0.001 - 99.99
- * Cycle: 0.05%
- * Unique TEACH function
- * Memory for time recorder
- * Liquid pressure adjustable: 0-120PSI (0-8KG)



HELPS TO
OPERATE



ADAPTOR TO
HOLD BARREL

PERISTALTIC DISPENSER: TOKii-800

Size: 190W x 184D x 94H
 Weight: 3.5kg
 Voltage: 110/220VAC, 50/60Hz
 Speed: 0~160RPM
 Time/ gelatinize Rolling: 0 - 999°
 Rolling/Back Rolling: 1-999°
 Min Dot: 0.0001 cc (ϕ 0.2* ϕ 0.7 Operation)
 10,000cps
 Liquid dens it : Under 10,000cps

