

TOKii-410SPM SOLDER PASTE MIXER



FEATURE

- Solder Paste Mixer
- Working voltage: AC220V (60HZ) 40W
- Operating speed: One operation: 1400RPM
- Secondary operation: 400RPM
- Machine size: 410 X 410 X 490MM (W.D.H)
- Time setting: 0.1-9.9 minutes, each adjustment for 0.1 minutes, 10-30 minutes, each adjustment for 1.0 minutes
- Work Ability: Mix 1 bottle or 2 bottles of 500 g solder paste at the same time

TOKii-CC774 SMT COMPONENT COUNTER



FEATURE

- SMT Parts Counter
- Power Supply: AC220V
- Function: 5000PCS /15S
- Rated Power : 30W

- Counting quantity: -99999~99999 pcs
- Machine Size: L774 X W350 X H184mm
- Weight : 10kg
- Ribbon Wheel Diameter: Any SMD ribbon wheel size can be used.
- Ribbon spacing: 2,4,8,12,12,16,20,24,28,32,36,40,44,48,52,56mm cycle setting.
- Belt width: 8,12,16,24,32,44,56mm

TOKii-IC1000 & IC600



FEATURE

- Inspection Conveyor. TOKii-IC1000 1 Meter/ TOKii-IC600 is 600mm
- Width adjustment range: 50~350mm (customizable)
- Power: 75W
- Rail length: 1000mm
- Dimensions: L1000x W670 X H880mm
- The 1-meter waiting board function inspection area has added a waiting board function in the middle of the 1-meter device. After the placement machine comes out, the board stays in the middle of the device for easy manual inspection of whether the placement machine is properly attached
- TOKii-IC1000 with light rack & TOKii-IC600 no light Rack